

CE-marked stainless butt hinges

Certified butt hinges for heavy duty usage



Grade 13 Stainless Butt Hinge
with two ball bearings

Size	75mm (3")	100mm (4")	100mm (4")	
Type	-	Grade 13	Grade 13	
Length	75mm	100mm	100mm	
Width open	50mm	75mm	75mm	
Thickness	2.0mm	3.0mm	3.0mm	
Material Grade	201	304	201	
Screw holes (screws supplied)	6	8	8	
Boxed Range	60 x 1 pair	40 x 1 pair	40 x 1 pair	
Satin	53300	531500740	531500740T	
Polished	5330P	5315P0740	-	
Electro-brassed	-	53150EB	-	



Grade 13 R10 Stainless Butt Hinge
with two ball bearings

Size	100mm (4")	100mm (4")	100mm (4")	
Type	Grade 13	Grade 13	Grade 13 SEC	
Length	100mm	100mm	100mm	
Width open	75mm	75mm	75mm	
Thickness	2.0mm	3.0mm	3.0mm	
Material Grade	304	201	304	
Screw holes (screws supplied)	8	8	8	
Boxed Range	40 x 1 pair	40 x 1 pair	40 x 1 pair	
Satin	53150R10	53150R10T	53150R10SEC	
Polished	5315PR10	-	-	
Electro-brassed	53150R10EB	-	-	



Grade 304 Security
Stainless Steel Butt Hinge

Size	100mm (4")			
Type	Grade 13			
Length	100mm			
Width open	75mm			
Thickness	3.0mm			
Material Grade	304			
Screw holes (screws supplied)	8			
Boxed Range	40 x 1 pair			
Satin	53150R10SEC			

CE-marked
UK quality control
UK service support
Quality materials

For sales call 01255 422333 or email sales@nico.co.uk

NiCo

Recommended Duty

In order to help you select the most suitable hinge for a particular application, we supply a guide to hinge fitting and usage.

HEAVY

High frequency of use by public or by others with little incentive to exercise care, and with a high chance of accident occurring and of misuse.

Hinge Maintenance

Hinges are supplied dry in order to ease handling and prevent the transfer of oily marks to hinges and doors during fitting. In most cases, hinges should be oiled immediately after installation. This and the occasional application of oil during service should significantly reduce wear.

Hinges with ball bearings require periodic lubrication to reduce friction and maintain efficiency.

Available to order

Products indicated with the Telephone Symbol are available to order only. Please ring for details and lead times.

NOTE: Please visit www.Nico.co.uk for 'Declarations of Performance'.

Also available



LOAD PRO door hinges

Heavy duty hinges for fire door applications



ISO 9001 Cert No: Q 09355

Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea
Essex CO15 3TJ, England.

Tel: 01255 422333

Fax: 01255 432909

E-mail: sales@nico.co.uk

Web: www.nico.co.uk

For sales call 01255 422333 or email sales@nico.co.uk