Construction Products Regulation 2011 Declaration of Performance



DOP Number NICO 4817

1. Unique identification code of the product-type:

4817 EB - 101mm Mild Steel LoadPro Butt Hinge, Electro-Brassed 4817 SN - 101mm Mild Steel LoadPro Butt Hinge, Satin Nickel 4817 ZY - 101mm Mild Steel LoadPro Butt Hinge, Yellow Zinc 4817 C - 101mm Mild Steel LoadPro Butt Hinge, Powdercoat 4817 CH - 101mm Mild Steel LoadPro Butt Hinge, Polished Chrome 4817 SS-S - 101mm Stainless Steel LoadPro Butt Hinge, Satin 4817 NP - 101mm Mild Steel LoadPro Butt Hinge, Nickel Plate 4817 ZP - 101mm Mild Steel LoadPro Butt Hinge, Zinc Plate 4817 S5 - 101mm Mild Steel LoadPro Butt Hinge, Supercoat 4817 PB - 101mm Mild Steel LoadPro Butt Hinge, Polished Brass 4817 SS-P - 101mm Stainless Steel LoadPro Butt Hinge, Polished

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

4817 EB 4817 NP 4817 SN 4817 ZP 4817 ZY 4817 S5 4817 C 4817 PB 4817 CH 4817 SS-P 4817 SS-S

- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
 For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)

Nico Manufacturing Ltd, 109 Oxford Road, Clacton-on-Sea, ESSEX, CO15 3TJ, United Kingdom

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): N/A
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: System 1
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard. EN 1935:2002 Notified product certification No. 2812 performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the certificate of constancy of performance of the product.
- 8. European Technical Assessment: N/A
- 9. Declared performance

| Essential characteristics – Self closing | Performance | Harmonised technical specification |
|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Initial friction torque with max. Door mass 120 Kg | 0.85Nm | EN 1935:2002 |
| Static load | | |
| Load deformation | Passed with a displacement under load: - lateral not more than 0.55mm - vertical not more than 0.54mm and a residual displacement after unloading lateral less than 0.11mm - vertical less than 0.22mm | |
| Overload | No breakage of any hinge leaf, knuckle, barrel or pin nor any cracking or deformation visible to normal or corrected vision - the hinged test element remained connected to the frame. | |
| Shear Strength | Passed with a lateral and vertical displacement after unloading not more than 1mm | |
| Hinges for use on fire resistant and/or smoke-control doors; | Grade 1: Suitable for use on fire/smoke resistant door assemblies. | |
| Essential characteristics – Durability | Performance | Harmonised technical specification |
| Durability | Passed a 200,000 cycles test with a maximum wear: - lateral Less than 0.03mm - vertical less than 0.5mm with a maximum frictional torque - after 20 cycles 1.10Nm - after the completion of 200,000 cycles 1.20Nm | EN 1935:2002 |
| Corrosion | EB & NP Grade 1: 24 hrs SN & ZP Grade 3: 96 hrs ZY, S5, C, PB & CH Grade 4: 240 hrs | |
| Dangerous Substances Annex ZA3 | The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations. | |

10.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Ian Harrison (Marketing Director)

Ian Harrison

Date of issue - 30th November 2020

Nico Manufacturing Ltd. Oxford Road, Clacton-on-Sea, ESSEX, United Kingdom