

NiCo

www.nico.co.uk

**LOAD/PRO** door hinges

lift-off hinges for fire door applications

**4715 Maintenance Free Grade 11
Offset Lift Off Hinge****98mm X 84mm OFFSET
LIFT OFF HINGE (HANDED)**

Ideal for use in high traffic areas, the 4715 provides maintenance free reliability for fire doors up to 80Kg.

The self-lubricating polymer bearing guarantees the right amount of lubrication over the life of the hinge and also eases alignment of the door and frame at installation.

**FEATURES & BENEFITS**

- Self lubricating polymer bearing
- Polymer bearings provide low co-efficient of friction
- Bearings guarantee the right lubrication for the life of the hinge
- Grade: 304 stainless steel or CS4 mild steel & Supercoat
- Ideal for use in high traffic environments
- Ideal for use with fingertrap protection
- Easy alignment of door leaf and frame during fitting
- Maximum adjusted door weight: 80kg
- Recommended minimum door thickness: 35mm
- Supplied with No.10 1¼" screws
- 25 year mechanical guarantee

TESTING & TECHNICAL

- Made in Britain to an ISO 9001 Quality System
- UKCA and CE marked
- EN 1935: 2002 Grade 11
- UKCA Certificate Nos: 1121-CPR-UK-AC7722/AC7723/AC7724
- CE Certificate Nos: 2812-CPR-AC0077/AC0078/AC0079
- Certifire 30 minute & 60 minute Assessment Report CF769
- 30 minute Warrington Fire Assessment Report WFAR176781
- 60 minute Fire tested in accordance with EN 1634-1

MADE IN BRITAIN

Quality materials

Choice of finishes

UKCA, CE & Certifire
approvalsISO 9001:2015
Manufacturer

ISO 9001 Cert No: Q.09355

**Nico Manufacturing Ltd**Oxford Road, Clacton-on-Sea
Essex CO15 3TJ, England.

Tel: 01255 422333

Fax: 01255 432909

E-mail: sales@nico.co.uk

Web: www.nico.co.uk

For sales, call 01255 422333 or email sales@nico.co.uk