

LOAD PRO door hinges

lift-off hinges for fire door applications

4720 Maintenance Free Grade 13 Lift Off Hinge



110mm X 98mm OFFSET LIFT OFF HINGE (HANDED)

Designed and engineered for long life performance in the most arduous conditions, the 4720 provides maintenance-free dependability on fire doors up to 120Kg.

With an 8mm pin for strength and a selflubricating polymer bearing to guarantee the right amount of lubrication over the life of the hinge, the 4720 ensures reliability and longevity in high-weight, high-traffic situations.



FEATURES & BENEFITS

- Self lubricating polymer bearing
- Polymer bearings provide low co-efficient of friction
- Bearings guarantee the right lubrication for the life of the hinge
- Grade: 304 stainless steel or CS4 mild steel & Supercoat
- Ideal for use in high traffic environments
- Ideal for use with fingertrap protection
- Easy alignment of door leaf and frame during fitting
- Maximum adjusted door weight: 120kg
- Recommended minimum door thickness: 44mm
- Supplied with No.10 11/4" screws
- 25 year mechanical guarantee

TESTING & TECHNICAL

- Made in Britain to an ISO 9001 Quality System
- UKCA and CE marked
- EN 1935: 2002 Grade 13
- UKCA Certificate Nos: 1121-CPR-UK AC7729/AC7715
- CE Certificate Nos: 2812-CPR-AC0084/AC0086/AC5069
- Certifire 30 minute & 60 minute Assessment Report CF769
- 60 minute Warrington Fire Assessment Report WFAR176781

MADE IN BRITAIN

Quality materials

Choice of finishes

UKCA, CE & Certifire approvals

ISO 9001:2015 Manufacturer







Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea Essex CO15 3TJ, England.

Tel: 01255 422333 Fax: 01255 432909 E-mail: sales@nico.co.uk

Web: www.nico.co.uk

For sales, call 01255 422333 or email sales@nico.co.uk