





# hinges for fire door applications

# **4815 Maintenance Free** Grade 12 & 13 Butt Hinge



LoadPro 4815 Hinge in polished Stainless Steel finish.

## 100mm X 88mm 2 BEARING BUTT HINGE

Available in both radius and square designs, the 4815 is engineered to the same exacting standards and testing as the rest of Nico's Hinge range.

Especially suited to high traffic environments, its maintenance free bearing guarantees the right amount of lubrication over the life of the hinge giving you a truly fit and forget product.



### **FEATURES & BENEFITS**

- Maintenance free bearing
- Grade: 304 stainless steel or CS4 mild steel & Supercoat
- Ideal for use in high traffic environments
- Ideal for use with fingertrap protection
- Maximum adjusted door weight: 120kg
- Recommended minimum door thickness: 44mm
- Supplied with No.10 11/4" screws
- 25 year mechanical guarantee

### **TESTING & TECHNICAL**

- Made in Britain to an ISO 9001 Quality System
- UKCA and CE marked
- EN 1935: 2002 Grade 12 (Steel), Grade 13 (Stainless Steel)
- UKCA Certificate Nos: 1121-CPR-UK AC7728/AC7730/AC7731
- CE Certificate Nos: 2812-CPR-AC0083/AC0089/AC0090
- Certifire 30min & 60min Assessment Report CF769
- 30min Warrington Fire Assessment Report WFAR176781
- 60min Fire Tested in accordance with EN 1634-1

MADE IN BRITAIN

**Quality materials** 

**Choice of finishes** 

UKCA, CE & Certifire approvals

ISO 9001:2015 Manufacturer







#### Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea Essex CO15 3TJ, England.

> Tel: 01255 422333 Fax: 01255 432909 E-mail: sales@nico.co.uk

Web: www.nico.co.uk

For sales, call 01255 422333 or email sales@nico.co.uk