



LOAD PRO door hinges

hinges for fire door applications

4817 Maintenance Free Grade 13 Butt Hinge



LoadPro 4817 Hinge in Supercoat 500 Zinc-plated finish.

101mm X 76mm 2 BEARING **BUTT HINGE**

Available in both radius and square designs, the 4817 Butt Hinge is engineered to the same exacting standards and testing as the rest of Nico's Hinge range.

Especially suited to high traffic environments, its maintenance free bearing guarantees the right amount of lubrication over the life of the hinge giving you a truly fit and forget product.

Certifire

FEATURES & BENEFITS

- Maintenance free bearing
- Grade: 304 stainless steel or CS4 mild steel & Supercoat
- Ideal for use in high traffic environments
- Ideal for use with fingertrap protection
- Maximum adjusted door weight: 120kg
- Recommended minimum door thickness: 44mm
- Supplied with No.10 11/4" screws
- 25 year mechanical guarantee

TESTING & TECHNICAL

- Made in Britain to an ISO 9001 Quality System
- UKCA and CE marked
- EN 1935: 2002 Grade 13
- UKCA Certificate No: 1121-CPR-UK AC7731
- CE Certificate No: 2812-CPR-AC0090
- Certifire 30min & 60min Assessment Report CF769
- 30 minute Warrington Fire Assessment Report WFAR176781
- 60 minute Warrington Fire Assessment Report WFAR176781

MADE IN BRITAIN

Quality materials

Choice of finishes

UKCA, CE & Certifire approvals

ISO 9001:2015 Manufacturer







Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea Essex CO15 3TJ, England.

Tel: 01255 422333 Fax: 01255 432909

E-mail: sales@nico.co.uk Web: www.nico.co.uk

For sales, call 01255 422333 or email sales@nico.co.uk