



steel butt hinges

Range of general building butts



Cranked Butt Hinge

Size	38mm (1.1/2")	50mm (2")	63mm (2.1/2")	75mm (3")	100mm (4")
Length	38mm	50mm	63mm	75mm	100mm
Width open	35mm	38mm	42mm	49mm	72mm
Thickness	1.4mm	1.4mm	1.6mm	1.6mm	1.8mm
Screw holes/size	4/5	4/6	6/6	6/7	8/8
Bulk Packed	250	500	400	100	40
Self-coloured	1838 0 22 01	1850 0 22 01	1863 0 22 01	1875 0 22 01	1900 0 22 01
Electro-brassed	1838 0 22 02	1850 0 22 02	1863 0 22 02	1875 0 22 02	1900 0 22 02
Zinc-plated	1838 0 22 04	1850 0 22 04	1863 0 22 04	1875 0 22 04	1900 0 22 04
LIGHT DUTY					



Flush Stormproof Hinge

Size	63mm (2.1/2")			
Length	63mm			
Cranked	18mm			
Thickness	1.8mm			
Screw holes	6			
Screw size	8			
Bulk Packed	200			
Supercoat 500	1815 S500			
MEDIUM DUTY				



Stormproof Hinge

Size	63mm (2.1/2")			
Length	63mm			
Cranked	11mm			
Thickness	1.8mm			
Screw holes	6			
Screw size	8			
Bulk Packed	200			
Zinc-plated	1820 0 22 04			
MEDIUM DUTY				

MADE IN BRITAIN
 UK service support
 Low carbon footprint
 Quality materials
 Choice of finishes
 ISO 9001:2015
 Manufacturer

For sales call 01255 422333 or email sales@nico.co.uk

Recommended Duty

In order to help you select the most suitable hinge for a particular application, we supply a guide to hinge fitting and usage.

LIGHT

Low frequency of use by those with high incentive to exercise care, for example, private house owners, and with small chance of accident occurring or misuse.

MEDIUM

Medium frequency of use by those with some incentive to use care, but some chance of accidents occurring and of misuse.

HEAVY

High frequency of use by public or by others with little incentive to exercise care, and with a high chance of accident occurring and of misuse.

Hinge Maintenance

Hinges are supplied dry in order to ease handling and prevent the transfer of oily marks to hinges and doors during fitting. In most cases, hinges should be oiled immediately after installation. This and the occasional application of oil during service should significantly reduce wear.

Available to order

Products indicated with the Telephone Symbol are available to order only. Please ring for details and lead times.



ISO 9001 Cert No: Q 09355

Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea
Essex CO15 3TJ, England.

Tel: 01255 422333

Fax: 01255 432909

E-mail: sales@nico.co.uk

Web: www.nico.co.uk



Loose Pin Butt Hinge

Size	75mm (3")	100mm (4")	100mm Radius	
Length	75mm	100mm	100mm	
Width open	49mm	72mm	72mm	
Thickness	1.6mm	1.8mm	1.8mm	
Screw holes	6	8	8	
Screw size	7	8	8	
Bulk Packed	100	40	40	
Self-coloured	☎1875 0 42 01	☎1900 0 42 01		
Electro-brassed	1875 0 42 02	☎1900 0 42 02		
Zinc-plated	☎1875 0 42 04	☎1900 0 42 04	☎1900 0 47 04	
MEDIUM DUTY				

Product Finishes

SC Self-coloured Code 01

Corrosion-resistance: None

Applications: Internal, secondary finish

EB Electro-brassed Code 02

Corrosion-resistance: Poor

Applications: Decorative, internal

Zn Zinc-plated Code 04

Corrosion-resistance: Good

Applications: Bright finish, internal

YZP Yellow Zinc-plated Codes 34, 54 & 64

Corrosion-resistance: Good

Applications: Internal & external

Other finishes are available on request.

For sales call 01255 422333 or email sales@nico.co.uk