

## Surface-mounted steel hinges for light duty




### Flush Hinge

Size	40mm (1.1/2")	50mm (2")	60mm (2.1/2")	75mm (3")
Length	40mm	50mm	60mm	75mm
Width	16mm	18mm	20mm	25mm
Thickness	1.0mm	1.2mm	1.2mm	1.6mm
Screw holes	4	4	5	6
Screw size	3	4	4	6
Bulk Packed	500	300	250	100
Electro-brassed	1940 0 11 02	1950 0 11 02	1960 0 11 02	1975 0 12 02
Florentine-bronzed	1940 0 11 03	1950 0 11 03	1960 0 11 03	1975 0 12 03
Zinc-plated	1940 0 11 04	1950 0 11 04	1960 0 11 04	1975 0 12 04
BOXED RANGE	-	12 x 25 pairs	12 x 25 pairs	-
Electro-brassed	-	1950 9 11 02	1960 9 11 02	-

**LIGHT DUTY**



### Single Cranked Hinge




Size	10mm (3/8")	16mm (5/8")		
Length	50mm	50mm		
Cranked	10mm	16mm		
Thickness	1.2mm	1.2mm		
Screw holes	7 (all to face)	7		
Screw size	4	4		
Bulk Packed	500	500		
Electro-brassed	0430 0 22 02	0410 0 22 02		
Florentine-bronzed	-	0410 0 22 03		
Zinc-plated	-	0410 0 22 04		

**LIGHT DUTY**



### Cranked Hinge



Size	5mm (3/16")			
Length	50mm			
Cranked	5mm			
Thickness	1.2mm			
Screw size	4			
Bulk Packed	500			
Electro-brassed	4160 0 22 02			
Zinc-plated	4160 0 22 04			

**LIGHT DUTY**

MADE IN BRITAIN  
 UK service support  
 Low carbon footprint  
 Quality materials  
 Choice of finishes  
 ISO 9001:2015  
 Manufacturer

## Recommended Duty

In order to help you select the most suitable hinge for a particular application, we supply a guide to hinge fitting and usage.

### LIGHT

Low frequency of use by those with high incentive to exercise care, for example, private house owners, and with small chance of accident occurring or misuse.

### MEDIUM

Medium frequency of use by those with some incentive to use care, but some chance of accidents occurring and of misuse.

## Hinge Maintenance

Hinges are supplied dry in order to ease handling and prevent the transfer of oily marks to hinges and doors during fitting. In most cases, hinges should be oiled immediately after installation. This and the occasional application of oil during service should significantly reduce wear.

## Product Finishes

### EB Electro-brassed Code 02

Corrosion-resistance: Poor

Applications: Decorative, internal

### FB Florentine-bronzed Code 03

Corrosion-resistance: Poor

Applications: Decorative, internal

### Zn Zinc-plated Code 04

Corrosion-resistance: Good

Applications: Bright finish, internal

Other finishes are available on request.



ISO 9001 Cert No: Q 09355

### Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea

Essex CO15 3TJ, England.

Tel: 01255 422333

Fax: 01255 432909


E-mail: sales@nico.co.uk

Web: www.nico.co.uk

# flush hinges




## Cranked Hinge



Size	9.5mm (3/8")			
Length	50mm			
Cranked	9.5mm			
Thickness	1.2mm			
Screw holes	4			
Screw size	4			
Bulk Packed	500			
Electro-brassed	2950 0 22 02			
Florentine-bronzed	2950 0 22 03			
Zinc-plated	2950 0 22 04			
<b>LIGHT DUTY</b>				



## Double Cranked Hinge



Size	16mm (5/8")			
Length	50mm			
Cranked	16mm			
Thickness	2.0mm			
Screw holes	8			
Screw size	4			
Bulk Packed	250			
Electro-brassed	4100 0 22 02			
Zinc-plated	4100 0 22 04			
<b>MEDIUM DUTY</b>				



## Finial Hinge

Size	50mm (2")	60mm (2.1/2")	75mm (3")	
Length	50mm	60mm	75mm	
Cranked	18mm	20mm	25mm	
Thickness	1.2mm	1.2mm	1.6mm	
Material	Steel/Mazak	Steel/Mazak	Steel/Steel	
Screw holes	4	5	6	
Screw size	4	4	6	
Bulk Packed	250	250	100	
Electro-brassed	1950 0 13 02	1960 0 13 02	1975 0 13 02	
Florentine-bronzed	1950 0 13 03	1960 0 13 03	-	
<b>LIGHT DUTY</b>				

## Available to order

Products indicated with the Telephone Symbol are available to order only. Call for details and lead times.

**For sales call 01255 422333 or email sales@nico.co.uk**