

NiCo

www.nico.co.uk




LOAD/PRO door hinges

Lift-off Hinges for fire door applications



4710 Lift Off Hinge

LoadPro 4710 Hinge in Yellow Passivate finish.




4710 – 85x76mm Symmetrical Lift Off Hinge (handed)

Grade 304 stainless steel or CS4 mild steel
EN 1935:2002 Grade 10
CE Certificate Nos. 1121-CPR-AC0074/AC0075/AC0076
Certifire 30min and 60min Assessment Report CF769
Warrington Fire Assessment Report 30min and 60min WFAR176781
Fire tested in accordance with EN 1634-1:2000 and CE Marked
Supplied with No. 10 1/4" screws
Maximum adjusted door weight: 60kg
Recommended minimum door thickness: 35mm



4715 Lift Off Hinge

LoadPro 4715 Hinge in Satin Nickel finish.



4715 – 98x84mm Offset Lift Off Hinge (handed)

Grade 304 stainless steel or CS4 mild steel
EN 1935:2002 Grade 11
CE Certificate Nos. 1121-CPR-AC0077/AC0078/AC0079
Certifire 30min and 60min Assessment Report CF769
Warrington Fire Assessment Report 30min and 60min WFAR176781
Fire tested in accordance with EN 1634-1:2000 and CE Marked
Supplied with No. 10 1/4" screws
Maximum adjusted door weight: 80kg
Recommended minimum door thickness: 35mm

MADE IN BRITAIN

UK service support

Low carbon footprint

Quality materials

Choice of finishes

CE & Certifire approvals

**ISO 9001:2015
Manufacturer**

For sales call 01255 422333 or email sales@nico.co.uk

Technical Data

The Load Pro range meets a broad range of high performance requirements.

Where on-site removal of the door is necessary, there are a choice of 5 hinge patterns each offering individual installation and performance characteristics.

Incorporating low-friction bearings to assist in the ease of door operation, Load Pro is the recommended choice for high efficiency specifications where conformity with the door opening resistance criteria of DDA (Disability Discrimination Act) is paramount.

Choice of Finishes


LOADPRO Hinges are available in the following finishes: Zinc Plated; Electro Brass Plated; Zinc Yellow Passivated; Satin Nickel Plated; Polished Brass; Chrome; Supercoat Corrosion-resistant Coating; Painted; Satin and Polished Stainless.

LOADPRO door hinges



4717 Lift Off Hinge

LoadPro 4717 Hinge in Mild Steel finish.



4717 – 98x84mm Symmetrical Lift Off Hinge (handed)

Grade 304 stainless steel or CS4 mild steel

EN 1935:2002 Grade 13

CE Certificate Nos. 1121-CPR-AC0080/AC0081/AC0082

Certifire 30min and 60min Assessment Report CF769

Warrington Fire Assessment Report 30min and 60min WFAR176781

Fire tested in accordance with EN 1634-1:2000 and CE Marked

Supplied with No. 10 1/4" screws


Maximum adjusted door weight: 100kg

Recommended minimum door thickness: 44mm



4718 Lift Off Security Hinge

LoadPro 4718 Hinge in Supercoat 500 finish.



4718 – 98x84mm Symmetrical Lift Off Security Hinge

CS4 mild steel

EN 1935:2002 Grade 12

CE Certificate Nos. 1121-CPR-AC0082

Certifire 30min and 60min Assessment Report CF769

Warrington Fire Assessment Report 30min and 60min WFAR176781

Fire tested in accordance with EN 1634-1:2000 and CE Marked

Supplied with No. 10 1/4" screws

Maximum adjusted door weight: 100kg

Recommended minimum door thickness: 44mm



ISO 9001 Cert No: Q 09355

Nico Manufacturing Ltd

Oxford Road, Clacton-on-Sea
Essex CO15 3TJ, England.

Tel: 01255 422333

Fax: 01255 432909

E-mail: sales@nico.co.uk

Web: www.nico.co.uk

For sales call 01255 422333 or email sales@nico.co.uk